

Pinch Pleated Draperies

Specifications

Fabric details	Meets commercial laundry standards; dry cleanable and fire retardant
Size	Custom sizes made to order based on room measurements
Style	Pairs or right/left panels both available as traversing or stationary
Mounts	Inside or outside, wall or ceiling
Operation	Baton, hand, or cord draw; stationary; baton loop or motorized (ADA)
Construction	Straight needled and sewn 1/2" from bottom of buckram using monofilament thread (5 pleats per 54" fabric width)
Pleats	3 finger pleat
Fullness	200% unless otherwise specified
Lining	Standard, Custom, 2-Pass Blackout, 3-Pass Blackout
Heading	4" Buckram, permanent finish, washable 5" Buckram on draperies over 108" (optional)
Seams	Pleat-marked with seams hidden behind the pleats For 3-Pass Blackout: free standing and French seamed
Bottom Hems	Face: 4" Single or double fold with blind stitched hems Lining: Overlocked bottom edge of lining
Side Hems	1.5" double turned
Weights	Square, covered weight sewn on each seam and corner of face fabric
Returns	3 1/2" standard 6" for double rod treatments 9" for 3-rod systems
Corners	Sew closures at bottom hem
Pins	Microflex 2000 adjustable pins or stainless steel
Packing	Fan folded. Steaming may be required for creasing
Warranty	1 year limited warranty against material & manufacturing defects